Grommets Ltd Unit 2, Hollands Lane Industrial Estate Henfield West Sussex BN5 9QY



www.grommets.co.uk

The second secon

ĭ sales@grommets.co.uk

MATERIAL DATA SHEET

<u> PVC - BLACK</u>

(POLYVINYLCHLORIDE)

	BS2782	UNIT	CONDITIONS	RESULTS
GENERAL PROPERTIES Density	620A	G/cm3	23°C	1.15 to 1.48
		·		
THERMAL PROPERTIES				
Cold Flex Temperature	150B	°C		-10 to -50
Service Temperature				
Minimum		°C		-30
Maximum (continuous / intermittent)		°C		50 to 70
MECHANICAL PROPERTIES				
Softness BSS Number	365A			20 to 120
Hardness		Shore A		40 to 90
Tensile Strength	320A	MPa		5 to 20
Elongation At Break	320A	%		250 to 450
Modulus at 100% extension	320A	MPa		2 to 15
FLAMMABILITY PROPERTIES				
Oxygen Index	4589			25 to 40
Flammability Rating	UL 94			HB – V0
CHEMICAL PROPERTIES				
Resistance to Weak / Strong Acids				Good / Bad
Resistance to Weak / Strong Alkalis				Good / Bad
Resistance to Organic Solvents				Bad
Resistance to Oils and Greases				Bad
Resistance to UV				Good

Grommets Ltd is in no way responsible for the application of its products by the end user and accepts no liability for damages or losses incurred by their application, which is beyond the control of Grommets Ltd. Please see our full T&C's available at www.grommets.co.uk



Our Products Grommets • Sleeved Grommets • Cable Entry Sleeves • Plugs • Bungs • Bushes Washers • Feet • Grips • Cord Rings • Ferrules • Discs • Edging Strip • Custom Moulding

/ www.grommets.co.uk



MD3 - ISSUE 6 - JAN 2017

Grommets Ltd is registered at Companies House England and Wales Company Number. 2842512 • VAT Number. GB 620 8409 58 The Grommets Limited logo is a registered Trade Mark. Trade Mark Number. UK00003164099

We are an ISO 9001:2008 registered company