

Grommets Ltd

Unit 2, Hollands Lane Industrial Estate
Henfield
West Sussex
BN5 9QY

+44 (0)1273 493 355 +44 (0)1273 493 388

sales@grommets.co.uk



www.grommets.co.uk

MATERIAL DATA SHEET

NEOPRENE RUBBER (BS2752 / C50) BLACK

ACTUAL PHYSICAL PROPERTIES

COLOUR	BLACK
HARDNESS RANGE	46 - 55 IRHD
TENSILE STRENGTH	12 MPa Min.
ELONGATION AT BREAK	400% Min.
COMPRESSION SET (24 HRS @ 70°C)	30% Max
DENSITY (SPECIFIC GRAVITY)	1.35

HEAT RESISTANCE

MAXIMUM TEMPERATURE	+ 110°C
MINIMUM TEMPERATURE	- 30°C

VOLUME SWELL (%)

FUEL B, 22HRS @ 40°C	0 TO 80
----------------------	---------

TEAR RESISTANCE	22 KG / CM
ABRASION RESISTANCE	160 MM3

Grommets Ltd is in no way responsible for the application of its products by the end user and accepts no liability for damages or losses incurred by their application, which is beyond the control of Grommets Ltd. Please see our full T&C's available at www.grommets.co.uk

MD5 - Issue 5 – JAN 2017



Our Products Grommets • Sleeved Grommets • Cable Entry Sleeves • Plugs • Bungs • Bushes
Washers • Feet • Grips • Cord Rings • Ferrules • Discs • Edging Strip • Custom Moulding

www.grommets.co.uk



Grommets Ltd is registered at Companies House England and Wales
Company Number. 2842512 • VAT Number. GB 620 8409 58

The Grommets Limited logo is a registered Trade Mark.
Trade Mark Number. UK00003164099

We are an ISO 9001:2008 registered company